



CHALLENGER from ENNIS FABRICS

Challenger has the soft feel of leather and demonstrates both durability and strength. Challenger performs well across numerous markets and testing parameters ensuring that it will become your go to vinyl in almost any application.

ACT PERFORMANCE INFORMATION:



Abrasion: 1,500,000+ Double Rubs

Content: 100% Polyvinyl Chloride (PVC)

Backing Content: 100% Polyester

Cold Crack: -55°C (-67°F)

Fire Retardancy: CALTB117-2013, IMO FTP Code

2010 - Part 8, MVSS302, NFPA 260 Class 1, UFAC Class 1

UV Resistance: AATCC 16.3 - Grade 4.0 (1,500 hours)

Width: 55" (140 cm) | **Roll Size:** 30 yd (27 m)

| | | |
|-------------------|------------------|----------------|
| 61 White Cap | 602 Mystic White | 91 Dove |
| 63 Vanilla | 605 Cream | 903 Fog |
| 609 Taupe | 802 Mocha | 805 Bark |
| 83 Tan | 87 Chestnut | 809 Chocolate |
| 902 Seagull | 905 Steel | 97 Slate |
| 908 Chincilla | 909 Raven | 37 Smokey Blue |
| 303 Denim Blue | 35 Royal | 306 Naval Blue |
| 308 Midnight Blue | 31 Lagoon | 54 Citron |
| 21 Meadow | 205 Spring | 24 Deep Teal |
| 44 Pumpkin Spice | 14 Cherry Red | 17 Garnet |
| 108 Wine | 109 Plum | 66 Diamond |
| 64 Pearl | 102 Champagne | 34 Spa |
| 86 Earth | 605 Cream | 804 Amber |
| | | 88 Tobacco |
| | | 98 Charcoal |

MPT Standard colours



* This information is offered for general guidance only. It is accurate to the best of our knowledge and is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with all laws and procedures applicable to the safe handling and use of this material.

Please note: The fabric and supply images displayed may not represent the actual product in its entirety.